


ICOM

VHF MARINE TRANSCEIVER

IC-M73EURO

***Slim, Stylish, Powerful VHF
with Professional Features***



**Last Call Voice
Recording**

The last call voice recording function automatically saves the last incoming call for 1 minute. You can also start recording manually. You will not miss an important call.



**Active Noise Cancelling
Technology**

The built-in bidirectional active noise cancelling reduces background noise to up to 90% and improves both your transmitted voice and incoming call. You will hear better and clearer!



**Bass Boost
Function**

The signal processing technology emphasizes low-pitched sound to provide a rich bass sound for both transmit and receive signals.



**700mW
Loud Audio**



**5W RF
Output Power**



**IPX8 Advanced
Waterproofing**

700mW Loud Audio

The IC-M73EURO uses a BTL (bridge-tied load) amplifier that doubles the audio output. Its internal speaker delivers a loud 700mW audio output with clear sound.

5W RF Output Power

The IC-M73EURO's 5 Watts of transmit power will provide reliable communication range for the user. A large capacity Lithium-Ion battery allows for 16 hours of operation, under normal conditions*.

* Typical operation with 5:5:90 duty ratio.

IPX8 Advanced Waterproofing

The IC-M73EURO continues to offer Icom's best waterproof protection. The radio has been tested to survive after being submersed in 1.5m depth of water for 30 minutes.

Slim, Hourglass Body Wide Viewing Angle LCD

The IC-M73EURO has a stylish, ergonomic design. A durable and rugged body provides user-friendly operation and long life. A wide viewing angle, high intensity LCD offers bright, easy to read characters.

Additional features

- AquaQuake™ water draining function
- Dual/Tri-Watch function for monitoring Channel 16 and/or call channel
- 4 level battery indicator
- Favorite channel and tag scan functions
- Optional waterproof speaker-microphones, HM-167 and HM-202
- Rapid charger BC-210 supplied
- Auto power save function

SPECIFICATIONS

GENERAL	
Frequency range	Tx 156.025–157.425MHz Rx 156.300–162.025MHz
Usable channel groups	INT, USA, WX channels
Type of emission	16K0G3E (FM)
Current drain (at 7.4V DC)	
Tx 5W output	1.4A
Rx Max. audio (Int SP/Ext SP)	450mA/250mA
Operating temp. range	–10°C to +55°C
Antenna impedance	50Ω (SMA)
Dimensions (W×H×D) (projections not included)	52.5×125×30 mm
Weight (approx.)	320g (With BP-245N, FA-S64V, MB-103)

Measurements made in accordance with AS/NZS 4115.2:2003. All stated specifications are subject to change without notice or obligation.

TRANSMITTER	
Output power (Hi/Mid/Low)	5W/3W/1W
Max. frequency deviation	±5.0kHz
Frequency stability	±10ppm
Spurious emissions	0.25μW
Adjacent channel power	70dB
Audio harmonic distortion	Less than 10% (at 60% dev.)
Residual modulation	40dB
RECEIVER	
Sensitivity (at 20dB SINAD)	–5dBμ emf typ.
Squelch sensitivity	–6dBμ emf typ. (at threshold)
Adjacent channel selectivity	65dB
Spurious response	65dB
Intermodulation	65dB
Hum and noise	40dB
Audio output power (at 10% distortion, 8Ω load)	700mW typ. (Internal SP @ 1kHz) 200mW (External SP)

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Applicable IP Rating

Ingress Protection Standard	
Water	IPX8 (Waterproof protection)

OPTIONS


Some options may not be available in some countries. Please ask your dealer for details.

BATTERY PACK



BP-245N Li-Ion 7.4V, 1900mAh (min.), 2000mAh (typ.).


RAPID CHARGER



BC-123SV **BC-210**

Charges the BP-245N in 2.5 hours (approx.).

MULTI-CHARGER



BC-197 **BC-157S**

Charges up to six BP-245N in 2.5 hours (approx.). AD-129 is supplied with the BC-197, depending on version.

Supplied Accessories:



- AC adapter, BC-123SV
- Battery pack, BP-245N
- Antenna, FA-S64V
- Rapid charger, BC-210
- Belt clip, MB-103
- Hand strap

SPEAKER-MICROPHONES



HM-167 **HM-202**
IPX8 rugged type IPX7 compact type

BELT CLIPS




MB-86 **MB-103**
Swivel type Alligator type

LEATHER BELT HANGERS



MB-96N **MB-96F**
Swivel type Fixed type

CIGARETTE LIGHTER CABLE & DC POWER CABLES



CP-25H **OPC-515L** **OPC-656**
For use with For use with For use with
BC-210 BC-210 BC-197

ANTENNA



FA-S64V

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia and/or other countries. AQUAQUAKE is a trademark of Icom Inc. (Japan) in the United States. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 www.icom.co.jp/world **Count on us!**

Icom America Inc.
2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone : +1 (425) 454-8155
Fax : +1 (425) 454-1509
E-mail : sales@icomamerica.com
URL : http://www.icomamerica.com

Icom Canada
Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone : +1 (604) 952-4266
Fax : +1 (604) 952-0090
E-mail : info@icomcanada.com
URL : http://www.icomcanada.com

Icom Brazil
Rua Pernambuco, 353 - Sala 901
Belo Horizonte, M.G.
30130-150, Brazil
Phone : +55 (31) 3582 8847
Fax : +55 (31) 3582 8987
E-mail : sales@icombrasil.com

Icom (Europe) GmbH
Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone : +49 (6196) 76685-0
Fax : +49 (6196) 76685-50
E-mail : info@icomeurope.com
URL : http://www.icomeurope.com

Icom Spain S.L.
Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone : +34 (93) 590 26 70
Fax : +34 (93) 589 04 46
E-mail : icom@icomspain.com
URL : http://www.icomspain.com

Icom Polska
81-850 Sopot, ul. 3 Maja 54, Poland
Phone : +48 (58) 550 7135
Fax : +48 (58) 551 0484
E-mail : icompolska@icompolska.com.pl
URL : http://www.icompolska.com.pl

Icom (UK) Ltd.
Blacksole House, Altira Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone : +44 (0) 1227 741741
Fax : +44 (0) 1227 741742
E-mail : info@icomuk.co.uk
URL : http://www.icomuk.co.uk

Icom France s.a.s.
Zac de la Plaine,
1 Rue Bréjondez des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone : +33 (5) 61 36 03 03
Fax : +33 (5) 61 36 03 00
E-mail : icom@icom-france.com
URL : http://www.icom-france.com

Icom (Australia) Pty. Ltd.
Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone : +61 (03) 9549 7500
Fax : +61 (03) 9549 7505
E-mail : sales@icom.net.au
URL : http://www.icom.net.au

Icom New Zealand
146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone : +64 (09) 274 4062
Fax : +64 (09) 274 4708
E-mail : inquiries@icom.co.nz
URL : http://www.icom.co.nz

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone : +886 (02) 2559 1899
Fax : +886 (02) 2559 1874
E-mail : sales@asia-icom.com
URL : http://www.asia-icom.com

Your local distributor/dealer: