



VHF MARINE TRANSCEIVER

IC-M88

Submersible

1m depth for 30 minutes

Intrinsically safe
versions available



Rugged
MIL-STD 810



Not Just Another Marine Radio!

Tough construction, superior waterproofing

The IC-M88 is built tough to withstand hazardous and inhospitable environments at sea and on land. Even if the IC-M88 is dropped into water, complete waterproofing* will protect it from harm. The compact and durable body has been tested to the military specifications (MIL-STD).

* Equivalent to JIS waterproof grade 7. (1m depth for 30 minutes)

Simple operation

6 clearly labelled buttons on the front panel and the volume/power knob maximize simplicity of operation. Even when wearing gloves, the large buttons are easy to operate. A large, clear LCD with backlighting and backlit buttons make night time operation simple.

Li-Ion battery for extra long battery life

With the standard 1700mAh Li-Ion battery pack, the BP-227, you can get up to 15 hours of talk time* without worrying about 'memory effect' on batteries. An optional AA alkaline battery case, BP-226, provides a convenient back up and great reassurance in an emergency.

* Typical operation; Tx:Rx:Stand-by duty ratio = 5:5:90

Waterproof speaker-microphone, HM-138

An optional waterproof speaker-microphone, the HM-138, provides reliable operation, even with the IC-M88 securely on your belt.

22 programmable channels for land use

The IC-M88 has 22 programmable channels reserved for Land use (146-174MHz). Wide/narrow channel spacing is programmable for each channel, and CTCSS and DTCS signaling is built-in.

*Appropriate license will be required.

Additional features

- Auto WX scan and WX Alert function (U.S.A. version only)
- Simple Up/Down switches for operating channel selection
- Instant access to Ch. 16 and Ch. 9 (or call channel)
- Simple add/delete TAG scanning operation
- Powerful 5W output
- 2 step power saver
- 4 level battery indicator
- The self check function checks internal temperature, connected battery voltage (over voltage detection), and water intrusion



Icom Inc.

Intrinsically safe versions approved by Factory Mutual Research Corporation



There are versions that conform to intrinsically safe rating of the FMRC (Factory Mutual Research Corporation). It can be used in many hazardous marine environments such as petroleum tankers and bulk cargo carrier. Ask your dealer for details.

Intrinsically safe : Class I, II and III, Division 1, Groups C, D, E, F, G
 Nonincendive : Class I, Division 2, Groups A, B, C, D hazardous locations when used with Icom BP-227FM battery pack. "Max. Temp. T3C at 40°C"
 Approved accessories: Speaker-microphone, HM-138

SPECIFICATIONS

GENERAL

- Frequency range :
 - Marine Tx 156.025–157.425MHz
 - Rx 156.050–163.275MHz
 - LMR Tx/Rx 146.000–174.000MHz
- Usable channels* (*Varies according to version):
 - All U.S.A., International and Canadian channels;
 - 22 LMR channels plus 10 weather channels
- Channel spacing :
 - Marine 25kHz
 - LMR 25/12.5kHz
- PLL channel step (LMR) : 5/6.25/7.5kHz
- Current drain (at 7.2V DC) :
 - Tx (at 5W output) 1.6A
 - Rx (at AF max.) 200mA
- Operating temp. range (except BP-227):
 - Marine -20°C to +60°C; -4°F to +140°F
 - LMR -30°C to +60°C; -22°F to +140°F
- Antenna impedance : 50Ω (SMA)
- Dimensions (W×H×D) : 62×97×39 mm; (proj. not included) 27¹/₁₆×3¹³/₁₆×1¹⁷/₃₂ in
- Weight (approx.; with BP-227): 280g; 9.9oz

TRANSMITTER

- Output power (Hi/Mid/Low) : 5/3/1W
- Max. frequency deviation :
 - Marine ± 5.0kHz
 - LMR (wide/narrow) ± 5.0/2.5kHz
- Audio harmonic distortion : Less than 10% (at 60% mod.)
- Spurious emissions : -70dBc typical
- Adjacent channel power :
 - Marine 70dB
 - LMR (wide/narrow) 70/60dB
- Hum and noise ratio :
 - Marine 40dB
 - LMR (wide/narrow) 40/34dB

RECEIVER

- Sensitivity (at 12dB SINAD) : 0.25μV typical
- Squelch sensitivity : 0.35μV typical (at threshold)
- Adjacent Ch. selectivity :
 - Marine 70dB typical
 - LMR (wide/narrow) 70/60dB typical
- Spurious response : 70dB typical

- Intermodulation rejection : 70dB typical
- Hum and noise ratio :
 - Marine 40dB
 - LMR (wide/narrow) 40/34dB
- Audio output power : 0.35W typical (at 10% distortion with an 8Ω load)

Applicable U.S. Military Specifications

Standard	MIL 810 C		MIL 810 D		MIL 810 E		MIL 810 F	
	Method	Proc.	Method	Proc.	Method	Proc.	Method	Proc.
Low Pressure	500.1	I	500.2	I,II	500.3	I,II	500.4	I,II
High Temp.	501.1	I	501.2	I,II	501.3	I,II	501.4	I,II
Low Temp.	502.1	I	502.2	I,II	502.3	I,II	502.4	I,II
Temp. Shock	503.1	I	503.2	I	503.3	I	503.4	I
Solar Radiation	505.1	I	505.2	I	505.3	I	505.4	I
Rain	506.1	I,II	506.2	I,II,III	506.3	I,II	506.4	I,II
Humidity	507.1	I,II	507.2	II,III	507.3	II,III	507.4	-
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-
Dust	510.1	I	510.2	I	510.3	I	510.4	I
Vibration	514.2	VIII, X	514.3	I	514.4	I	514.5	I
Shock	516.2	I, II, V	516.3	I, IV	516.4	I, IV	516.5	I, IV

- Supplied accessories: (*Varies according to version.)
- Battery pack • Battery charger • AC adapter*
 - Swivel belt clip • Antenna, FA-S59V • Hand strap

Measurement made in accordance with TIA/EIA-603. All stated specifications are subject to change without notice or obligation.

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

BP-226 BATTERY CASE

Battery case for AA (LR6)×5 alkaline cells. Water resistant, equivalent to JIS Grade 4.

BP-227/BP-227FM BATTERY PACK

7.2V/1700mAh Li-Ion battery pack. Provides 15 hours operating time* (approx. at 5 Watts). Same as supplied. Operating temp. range: -20°C to +60°C; -4°F to +140°F

* Tx (Hi): Rx: standby=5:5:90

BC-152 DESKTOP CHARGER

+ BC-147A/E AC ADAPTER
 Regularly charges the BP-227, BP-227FM in 9-10 hours. Same as supplied.

BC-119N DESKTOP CHARGER

+ AD-100 CHARGER ADAPTER
 + BC-145A/E/V AC ADAPTER
 For rapid charging of battery pack. An AC adapter is supplied depending on version. Charging time: 2.5-3 hours.

BC-121N MULTI-CHARGER

+ AD-100 CHARGER ADAPTER
 + BC-157 AC ADAPTER
 For rapid charging of up to 6 battery packs (Six AD-100s are required). Charging time: 2.5-3 hours.

CP-17L CIGARETTE LIGHTER CABLE WITH NOISE FILTER

OPC-515L DC POWER CABLE
 For use with the battery charger, BC-152 or BC-119N, instead of the AC adapter. (12-16 V DC required)

OPC-656 DC POWER CABLE
 For use the BC-121N with a DC power supply. (12-16V DC required)

HM-138 SPEAKER-MICROPHONE
 Full sized speaker-microphone. Equivalent to IPX7.

HM-168 SPEAKER-MICROPHONE
 Compact type speaker-microphone. Equivalent to IPX7.

MB-86 SWIVEL BELT CLIP
 Swivel belt clip. The same as that supplied.

MB-98 BELT CLIP Alligator type belt clip.

MB-96N LEATHER BELT HANGER
 Swivel type belt hanger.

MB-96F LEATHER BELT HANGER
 Fixed type belt hanger for use with MB-98.



Icom Inc. 1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

2380 116th Avenue NE, Bellevue, WA 98004, U.S.A.
 Phone : +1 (425) 454-8155
 Fax : +1 (425) 454-1509
 E-mail : sales@icomamerica.com
 URL : <http://www.icomamerica.com>

Icom New Zealand

146A Harris Road, East Tamaki, Auckland, New Zealand
 Phone : +64 (09) 274 4062
 Fax : +64 (09) 274 4708
 E-mail : inquiries@icom.co.nz
 URL : <http://www.icom.co.nz>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.
 Phone : +44 (0)1227 741741
 Fax : +44 (0)1227 741742
 E-mail : info@icomuk.co.uk
 URL : <http://www.icomuk.co.uk>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road, Taipei, Taiwan, R.O.C.
 Phone : +886 (02) 2559 1899
 Fax : +886 (02) 2559 1874
 E-mail : sales@asia-icom.com
 URL : <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada

Glenwood Centre #150-6165 Highway 17, Delta, B.C., V4K 5B8, Canada
 Phone : +1 (604) 952-4266
 Fax : +1 (604) 952-0090
 E-mail : info@icomcanada.com
 URL : <http://www.icomcanada.com>

Icom (Europe) GmbH

Communication Equipment Himmelgeister Str. 100, D-40225 Düsseldorf, Germany
 Phone : +49 (0)211 346047
 Fax : +49 (0)211 333639
 E-mail : info@icomeurope.com
 URL : <http://www.icomeurope.com>

Icom France s.a.s.

Zac de la Plaine, 1 Rue Brindejonc des Moulinais, BP 45804, 31505 Toulouse Cedex 5, France
 Phone : +33 (5) 61 36 03 03
 Fax : +33 (5) 61 36 03 00
 E-mail : icom@icom-france.com
 URL : <http://www.icom-france.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road, Clayton, VIC 3168 Australia
 Phone : +61 (03) 9549 7500
 Fax : +61 (03) 9549 7505
 E-mail : sales@icom.net.au
 URL : <http://www.icom.net.au>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer" 08190, Sant Cugat del Valles, Barcelona, Spain
 Phone : +34 (93) 590 26 70
 Fax : +34 (93) 589 04 46
 E-mail : icom@icomspain.com
 URL : <http://www.icomspain.com>

Icom Polska

Sopot, 3 maja 54, Poland
 Phone : +48 (58) 550 7135
 Fax : +48 (58) 551 0484
 E-mail : icompolska@icompolska.com.pl
 URL : <http://www.icompolska.com.pl>